

SAFETY DATA SHEET

ENGRO CORPORATION LIMITED Afro Asia Building, 63 Robinson Road #17-03, Singapore 068894 Tel: (65) 6561 7978 Fax: (65) 6561 9770

www.engro-global.com

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name/ Category: PreFine Cement

Other Designation: PreFine 60 / 80

Description: PreFine Cement is a supplementary cementitious material

based on microfine cement developed for special applications, such as injection and grouting. PreFine 60 / 80 has an excellent penetration into micro cracks and provides efficient tightness

combined with good durability.

CAS Reg. No.: NA (Mixture)

Supplier: EnGro Corporation Limited

2. HAZARDS IDENTIFICATION

Category Classification(s): SKIN CORROSION/IRRITATION - Category 1

EYE DAMAGE - Category 1

SKIN SENSITIZATION - Category 1

CARCINOGENICITY/INHALATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

[Respiratory tract irritation] - Category 3

GHS label elements

Hazard pictograms:







Signal word: Danger

SDS_PF60/80 Page 1 of 6 Rev.07 (23 Apr 25)



Hazard statements: H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H335 - May cause respiratory irritation.

H350 - May cause cancer.

Precautionary Statements: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash clothing, face and hands thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear eye protection, protective clothing and protective gloves.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Nature: Blended cement from Portland cement and Ground Granulated Blast

Furnace Slag (GGBS)

| Ingredients | Name | CAS | Proportion |
|-------------|-----------------|------------|------------|
| | Portland Cement | 65997-15-1 | 30-50% |
| | GGBS | 65996-69-2 | 50-70% |
| | Other Additives | | 0-2% |

4. FIRST AID MEASURES

Eye Contact The product must be washed out of the eyes without any delay with clean running

water whilst holding the eyelid open. Take care not to wash the product from one eye to

the other. Use plenty of water for at least 10 minutes.

If symptoms persist obtain medical assistance without delay.

Skin Contact Prolonged contact may cause irritation or in severe cases cement burns, this is increased

with splashes on clothes or overalls. These should be laundered before re-use.

ALL CHEMICAL PRODUCTS SHOULD BE HANDLED WITH CARE. Wash all splashes immediately from the skin with plenty of clean water and soap; if any other skin

symptoms occur obtain medical assistance.

Ingestion DO NOT INDUCE VOMITING. Give one pint of water to drink and obtain medical

attention without delay.

Inhalation After inhalation of dust. Keep patient calm, remove to fresh air. If difficulties occur:

Obtain medical attention.

SDS_PF60/80 Page 2 of 6 Rev.07 (23 Apr 25)



5. FIRE FIGHTING MEASURES

Suitable extinguishing agents: Select to suit surrounding area

Additional information: Product is not combustible. Only the packaging will result to fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precaution Avoid dust formation and avoid contact with skin and eyes. Use

personal protective clothing. Ensure adequate ventilation

Environmental precautions Prevent large volumes from passing into the drain, watercourses or

small pools of water

Measure for cleaning To prevent dust creation, cement should be vacuumed away. Cement

that has been mixed with water sets and can be disposed as per normal under in accordance with federal, state and local regulations (FP N)

7. HANDLING AND STORAGE

Handling/Storage Precautions Keep in dry, cool & well-ventilated area as water contact will initiate set.

Avoid generation or accumulation of dusts. Use local exhaust extraction.

Work/Hygienic Practices Wash thoroughly after using product.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Engineering Controls General ventilation and/or local exhaust recommended.

Hygienic Measures EXPERTS ALWAYS WEAR THE RIGHT PROTECTIVE CLOTHING. Personal protective

equipment must be inspected regularly and prior to each use. Replace if

necessary

Always wash hands before eating, drinking, smoking or using the toilet and after

finishing work. Observe good housekeeping and general hygiene guidelines.

Eye/Face Protection Safety goggles

Skin Protection Light gloves. Suitable work wear should be worn to protect personal clothing,

e.g. cotton overalls buttoned at neck and wrist. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust

when removing or laundering clothes.

Respiratory Protection Dust mask.

SDS_PF60/80 Page 3 of 6 Rev.07 (23 Apr 25)



9. PHYSICAL AND CHEMICAL PROPERTIES

Form powder

Colour Grey

Odour No odour

Boiling Point Not Applicable

Flash Point Non Flammable

Vapour Pressure (MM Hg/70 F) Not Applicable

Vapour Density (Air=1) Not Applicable

Specific Gravity Approximately 2.90

pH 12-14

Evaporation Rate and RefNot Applicable

Solubility in Water Slight soluble

Percent Volatile by Volume 0

10. STABILITY AND REACTIVITY

Thermal decomposition / Product is stable and no decomposition may occur if stored and handled

as prescribed/indicated.

Conditions to be avoided See MSDS section 7 - Handling and storage

11. TOXICOLOGICAL INFORMATION

Eye Contact Dry cement dust or the fumes from the mixture of cement and water can quickly cause

serious eye damage. Splashes into the eyes can cause corneal edema

Skin Contact Prolonged contact may cause irritation or in severe cases cement burns

Ingestion Can cause irritation in the mouth or the digestive system. Chronic bronchitis may result

from long term exposure

Inhalation Inhalation of cement dust can cause irritation to mucous membrane

SDS_PF60/80 Page 4 of 6 Rev.07 (23 Apr 25)



12. ECOLOGICAL INFORMATION

The product has no known ecotoxicity effect

13. DISPOSAL CONSIDERATIONS

Product Disposal Observe national and local legal requirements. Residues should be disposed of

in the same manner as the substance/product.

Packaging Disposal Dispose of contaminated packaging with care. Empty containers may contain

hazardous residues. Completely emptied packaging can be given for recycling

14. TRANSPORT INFORMATION

The product is not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID) and therefore no classification is required.

15. REGULATORY INFORMATION

Hazard symbol(s)

Xi Irritant

R-phrase(s): -

R37/38 Irritating to respiratory system and skin

R41 Risk of serious damage to eyes

S-phrase(s): -

S2 Keep out of the reach of children

S22 Do not breathe dust

S24/25 Avoid contact with skin and eyes.

In case of contact with eyes rinse immediately with plenty of water and seek

medical advice.

S37/39 Wear suitable gloves and eye/face protection.

SDS_PF60/80 Page 5 of 6 Rev.07 (23 Apr 25)



16 OTHER INFORMATION

These SDS summaries at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since EnGro Corporation Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard term and conditions, a copy of which is sent to our customers and is also available upon request.

Supplier's Address:

ENGRO CORPORATION LIMITED

Afro Asia Building,
63 Robinson Road #17-03, Singapore 068894

Tel: (65) 6561 7978 Fax: (65) 6561 9770

Note: EnGro Corporation Limited does not certify the data on the SDS. The certified values for this material are given only as a reference from the EnGro Corporation Certificate of Analysis.

SDS_PF60/80 Page 6 of 6 Rev.07 (23 Apr 25)